

Electric Pallet Truck **SWP-2500/3000 Series**



The most powerful unit in SWP Series.



▷ Safety Beacon



▷ New Handle TEMO
Made in Germany for more comfort operation



▷ Powder Coating



▷ Fork house modification



▷ Stainless steel fork for Clean room

Specifications

Model	Unit	SWP-2500	SWP-3000
Load Capacity ☆	kg	2500	3000
Load Center	mm	575	575
Max. Lifting Height	mm	205	205
Min. Lifting Height	mm	85	85
Gradeability	%	8	5
Overall Length	mm	2091	2164
Overall Width	mm	750	750
Overall Height	mm	1360	1360
Wheel Base	mm	1150	1150
Fork Length	mm		1150
Fork Width	mm		175
Fork Spread	mm	680	680
Weight (Incl. Battery)	kg	625	660
Turning Radius	mm	1870	1929
Travel Speed	With / Without Load	km/hr	3~4/ 5~6
Motor	Drive	kw	AC 16Vx1.5kw
	Hydraulic	kw	DC24Vx2.2kw
Battery	-	24Vx170Ah/5Hr	24Vx201Ah/5Hr
	-		AC1Φx220V, 50/60Hz
Control	Drive	-	F.E.T Control Type
	Hydraulic	-	Magnetic Contactor Type

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.

Electric Pallet Truck **SWP-2000** Series



Demonstrate the superior ability to work in a small space.

Features

- Compact design combined with new technology, making this product ideal for narrow, cramped aisles.
- The shortest head length among competitors gives the best possible maneuverability.
- Smooth speed control with advanced technology.
- Powerful traction battery.
- Drive unit with electromagnetic brake.
- Battery charger installed (Built-in type)



▷ Safety Beacon



▷ New Handle TEMO
Made in Germany for more comfort operation

Specifications

Model		Unit	SWP-2000
Load Capacity ☆		kg	2000
Load Center		mm	600
Max. Lifting Height		mm	205
Min. Lifting Height		mm	85
Gradeability		%	10
Overall Length		mm	1937
Overall Width		mm	730
Overall Height		mm	1270
Wheel Base		mm	1150
Fork Length		mm	1150
Fork Width		mm	175
Fork Spread		mm	680
Weight	With / Without Battery	kg	570/412
	Turning Radius	mm	1740
Travel Speed	With / Without Load	km/hr	3~4/5~6
Lifting Speed	With / Without Load	mm / s	20/23
Motor	Drive	kw	AC 16Vx1.5kw
	Hydraulic	kw	DC 24Vx2.2kw
Battery		-	24Vx170Ah/5Hr (158kgx1EA)
	Battery Charger	-	1Φx220V, 50/60Hz
Control	Drive	-	F.E.T Control Type
	Hydraulic	-	Magnetic Contactor Type

☆ Based on the rated load center.

※ The above appearance and specifications are subject to change without prior notice.