



Movable Table Lift

LT-Manual/Electric Series

To minimize labor's Fatigue

In the Machine Tool and private working lines, lessen the Labor's fatigue without repeated bending the body during loading and unloading.



● Spec.

Model	Unit	LT-35S	LT-50	LT-100	LT-100S
		2 stage	1 stage	1 stage	2 stage
Load capacity	kg	350	500	1000	1000
Max.Lifting Height	mm	1340	1010	1000	1730
Min.Lifting Height	mm	355	300	380	490
Table Length	mm	900	900	1200	1200
Table width	mm	515	600	610	610
Footsteps on lifting	mm	37	28	20	25
Weight	kg	113	84	154	230

※The above specification are subject to change without prior notice.

LT-Electric series



● Spec.

Model	Unit	LT-50D	LT-50SD	LT-80D	LT-80SD
		1 stage	2 stage	1 stage	2 stage
Load Capacity	kg	500	500	800	800
Max.Lifting Height	mm	1000	1730	1000	1730
Min.Height of Table	mm	380	490	380	490
Table Length	mm	1200	1200	1200	1200
Table width	mm	610	610	610	610
Motor		12V x 0.8kw		12V x 0.8kw	
Battery		12Vx100Ah		12V x 100Ah	
Charger		1φ x 220V,60Hz		1φ x 220V,60Hz	
Weight	kg	262	350	262	350

※The above specification are subject to change without prior notice.



46-39, Robotland-Ro, 249 Beon-Gil, Seo-Gu, Incheon, Korea 22756

TEL : 032)820-5160 / FAX : 032)582-7513

web : www.soosung.com / e-mail : soosung@soosung.com