



Electric Baby Crane

SBC-Series

Multi and almighty function required!

Designed to drive Electrically with Electric rotating Boom and operated by Electrically-Hydraulic for lifting and lowering. To keep Crane safe, Outrigger installed and Platform could be custom-made. Up to 2 stage Boom, operated by Hydraulic-Electric and for 3 stage Boom, Manually operated.



Model		Unit	SBC-1000
Load capacity	1-Stage	kg	800
	2-Stage	kg	420
	3-Stage	kg	300
Platform size	Length	mm	980
	Width	mm	960
	Height	mm	270
Overall Length		mm	2302
Overall Width		mm	1200
Overall Height		mm	2149
Turning radius		mm	1997
Self Weight		kg	1800
Boom Length	1-Stage	mm	1000
	2-Stage	mm	2060
	3-Stage	mm	2700
Boom Height	1-Stage	mm	2500
	2-Stage	mm	2900
	3-Stage	mm	3300
Boom Turning Angle		Degree	180
Boom turning type			Hydraulic
Power			DC24V
Travel Speed	With Load	Km/h	4~5
	Without Load	Km/h	5~6
Motor	Boom	Kw	DC 24V 2.2kW
	Drive	Kw	AC 16V 1.5kW
	Boom Turning		H-100
Battery			24V x 268Ah/5Hr
Charger			AC 1φ x 220V x 50/60Hz
Control System			F.E.T / MAGNETIC CONTACTOR TYPE

Subject to change without prior notice.



Address: 46-39, Robotland-Ro, 249 Beon-Gil, Seo-Gu, Incheon, Korea 22756
 Tel : +82-32-820-5160 / Fax : +82-32-582-7513
 Web : www.soosung.com / e-mail : soosung@soosung.com

Examples for Special Application



Address: 46-39, Robotland-Ro, 249 Beon-Gil, Seo-Gu, Incheon, Korea 22756
 Tel : +82-32-820-5160 / Fax : +82-32-582-7513
 Web : www.soosung.com / e-mail : soosung@soosung.com